



720
"Flexible Edge Seal"

Spec Sheet

Last revised: August, 2003

Material Composition:

720 consists of a flexible graphite material covered on the top and both sides with a flexible PVC protective coating and co-extruded with a single soft elastomeric fin.

Colors:

This material is available in charcoal (black), dark brown, tan, gray, and white. Special colors available upon request, but may result in a surcharge.

Size:

720 is a flexible product. It is supplied in rolls.

Product Dimensions:

720 1/16" x 5/8" is standard. Other dimensions may be manufactured upon request. There will be surcharges for other dimensions .

Available Lengths:

Supplied in rolls up to and including 100'.

Temperature Exposure:

720 will remain flexible in a wide range of temperatures. The following is a guideline for properties of PVC. Environmental conditions and placement of the product may alter these temperature ranges.

Cold:

720 should remain flexible to -30 degrees F.

Hot:

720 should remain flexible to 140 degrees F.

Chemical Exposure:

PVC resists most acids, strong Alkalis, salts and paraffinic hydrocarbon solutions. It is not recommended for use with chlorinated or aromatic hydrocarbons, esters or polar solvents such as ketones.

Expansion Characteristics:

Products containing intumescent materials will expand at a variety of rates and temperatures. The following information serves as a guideline. Environmental conditions and placement of the product may alter these temperature ranges.

Temperature for Expansion:

390 degrees F

Rate of Expansion:

7:1 average

Moisture Resistance:

Good resistance to water and humidity.

Special Handling Requirements:

720 should be stored at ambient temperatures between 40 degrees F and 140 degrees F. The adhesive backing used on 720 has a shelf life of 18 months. Stocks should be rotated to accommodate this aging.