

4500 SVR EXIT DEVICE CHASSIS TEMPLATE

FOR USE WITH SVR & LBR DEVICES

(FOR PANIC AND FIRE RATED DEVICES)

(REV: 03)
 DWG NO: T-ED00044
 26490171

THIS SIDE UP FOR LHR DOOR

FOLD HERE

FOLD AND PLACE ON DOOR EDGE OR STOP FACE

PLACE THIS SIDE ON DOOR

4 3/8" [111]

DOOR EDGE OR STOP FACE

DOOR

1 21/32" [42]

1 9/16" [40]

2 7/16" [62]

3 7/32" [82]

(4x) METAL: DRILL/TAP FOR 1/4"-20 MACHINE SCREWS.
 WOOD: PRE-DRILL 1/8" HOLES.
 SEXBOLTS: DRILL 5/16" CLEARANCE HOLES ON PUSH SIDE,
 3/8" HOLES ON PULL SIDE.
 TRIM: DRILL 5/16" CLEARANCE HOLES ON PUSH SIDE,
 1/2" HOLES ON PULL SIDE.

5/8" CLEARANCE HOLE FOR BE & CE TRIM.
 NOT REQUIRED FOR DUMMY TRIM.
 FOR NL TRIM SEE INSTRUCTIONS/TEMPLATE
 FOR HOLE REQUIREMENTS.

(2x) METAL: DRILL/TAP FOR 1/4"-20 MACHINE SCREWS.
 WOOD: PRE-DRILL 1/8" HOLES.
 SEXBOLTS: DRILL 5/16" CLEARANCE HOLES ON PUSH SIDE,
 3/8" HOLES ON PULL SIDE.

DEVICE & STRIKE \varnothing

40" [1016]
 RECOMMENDED HEIGHT MAY BE
 DETERMINED BY DESIGN SPEC'S

FINISHED FLOOR

19/32" [15]

1 3/16" [30]

19/32" [15]

AFTER EXIT DEVICE IS CUT AND
 MOUNTED, INSTALL END CAP
 BRACKET CENTERED ON DEVICE \varnothing

 HOLE LOCATIONS

PRIMARY DIMENSIONS SHOWN IN INCHES,
 DIMENSIONS IN [] ARE MILLIMETERS.

THIS SIDE UP FOR RHR DOOR

